

COMMAND PTT 30

PTT 30

Light Weight Design

The PTT 30 Series of PTTs (Push-To-Talk) is designed for simple and comfortable use. It has a handy form factor and its light weight constitution makes the PTT 30 Series PTTs the perfect match for air traffic controllers and command centers.

As any COMMAND PTT series, the PTT 30 series is highly customizable for any specific needs in the communication set up. Its stable and recessed push to talk button ensures precise and reliable PTT signaling for crystal clear speech in critical situations when it matters most.

See compatible headsets at eposaudio.com/command-headsets



Key benefits & features

Light weight device

Comfortable and easy use for hours of use with high focus

Modular design

The PTT 30 comes with many different wiring options for any kind of set-up

Recessed button

Prevent accidental activation of the PTT button with a recessed button for maximum precision

Comfortable and easy button activation

Ergonomic button activation optimized for precise communication

COMMAND PTT 30

Product data

| Feature Matrix | PTT 30 | PTT 31 | PTT 32 | PTT 33 P |
|--------------------------------------|---------------------------------------|---------------------------------------|---------------------------------------|---------------------------------------|
| Integrated top cable | x | - | - | x |
| Mini-XLR socket for top cable | - | x | x | - |
| With mic pre-amp | - | - | x | - |
| Power feed-through to ANC | - | - | - | x |
| ANC on/off switch | - | - | - | x |
| Dimensions | 55 x 35 x 18 mm (L x W x D) | 70 x 35 x 18 mm (L x W x D) | 70 x 35 x 18 mm (L x W x D) | 55 x 35 x 18 mm (L x W x D) |
| General | | | | |
| Connection to headset | Direct cabling | Mini-XLR | Mini-XLR | Direct cabling |
| Signal processing | None | None | Analog | None |
| Microphone pre-amp gain | N/A | N/A | Max 17 dB | None |
| Gain preset | N/A | N/A | 14 dB | N/A |
| Required supply voltage to PTT | N/A | N/A | 8-16 VDC | N/A |
| Mic pre-amp output impedance | N/A | N/A | 150 ohm | N/A |
| Supply voltage to headset microphone | 8-16 VDC | 8-16 VDC | 2-3 VDC | 8-16 VDC |
| PTT signalling | Short-circuit of 2 configurable wires | Short-circuit of 2 configurable wires | Short-circuit of 2 configurable wires | Short-circuit of 2 configurable wires |

Cable options

Top cable

HM-series headsets:

- Typically Cable-III-6 (1001068) with a length of 0.8m is wired directly into PTT 30 Series

SC series headset:

- 6 pin Mini XLR plug integrated in headset cable

Bottom cable

- Typically coiled cable 0.47 m, extendable to 2 m
- Plug is typically 8 or 10 pin, straight or angled
- EPOS is able to customize cable assemblies and connector types to customer specification.

