

COMMAND 330 AG

Single-sided, in-ear headset for ATC and C3 operators. It provides premium sound quality through an earbud transducer and clear voice transmission via a noise-cancelling microphone. Its lightweight design allows all-day use without wearing fatigue.



Key Features

Premium all-day comfort with a lightweight design

Lightweight construction reduces wearing fatigue while a soft earhook and exchangeable silicone tips ensure great comfort and fit.

Tailored customization options for EPOS PTTs

The bottom cable can be pre-configured to operate with EPOS push-to-talk units, ensuring compatibility with existing equipment.

Natural listening experience

EPOS Sound™ technology, integrated into this comfortable in-earbud, provides clear voice reception for optimal communication.

Protect your hearing from sudden sound bursts

EPOS ActiveGard™ is a unique technology that protects your hearing from acoustic shock while preventing communication drop-out.

Clear voice transmission for safe communication

The advanced noise-cancelling microphone effectively eliminates background noise, ensuring optimal voice and speech clarity.

Additional benefits & features



Wearing flexibility

The adjustable boom arm can be rotated for flexible wearing on either ear



Removable earbud tips

Provided silicone tips can be separated to adapt to any existing custom earpieces



Designed and tested to last

A flexible boom arm and a secure interconnector make it a reliable working tool.



Reduce acoustic brain fatigue

Designed to provide the best conditions for your brain in noisy environments.



Two-year warranty

The headset is backed by EPOS two-year international warranty

Product data

1/2

Product

Art. no.	1001242
EAN code	57 14708 01049 4
UPC code	8 40064 41049 6

General

Wearing style	Single-sided
Ear coupling	In-Ear
Weight of headset	28 g / 0.98 oz
Storage temperature	-25 °C to +70 °C/ -13°F to +158 °F
Operating temperature	-25 °C to +70 °C/ -13 °F to +158 °F
Warranty	2 years

COMMAND 330 AG

Product data

2/2

Speaker Specifications

Sound pressure level:

dB SPL @ 1 KHz, 0.5 V

105

dB SPL @ 1 KHz, 1 mW

104

dB SPL @ 1 KHz, 1V

88

Max SPL [dB]

105*

THD, total harmonic distortion at 95 dB SPL at 1 kHz

< 1 %

Frequency response

80 - 16.0000 Hz

Impedance

150 Ω

* Limited by EPOS ActiveGard®

Product data

Microphone Specifications

Microphone type	Electret
Sensitivity	-40 dB re. 1 V/Pa, +/- 2.5 dB
Pick-up pattern	Noise-cancelling, uni-directional
Supply voltage	1.5 - 9 VDC
Frequency response	100 - 10,000 Hz
Output voltage	10 mV/Pa
Recommended load resistance	150 - 2,200 Ω

Product data

Packaging

Dimension of product packaging (W x H x D)	208 x 30 x 70 mm 8 x 1 x 2 in
Package weight (incl. complete product and packaging)	90.5 g / 31.92 oz
Units in distributor master carton	25
Master carton weight incl. products	2.69 kg / 5.93 lbs
Dimension of master carton (W x H x D)	370 x 180 x 220 mm 14.57 x 7.09 x 8.66 in
Unit pack/end user	1

Product

COMMAND 330 AG

What's in the box

Lightweight single-sided, in-ear headset, 1 x wind screen, 3 x earbud tips (S, M, L), Safety Guide, Quick Guide