

# COMMAND 330 AG

Single-sided, in-ear headset for ATC and C3 operators. It provides premium sound quality through an earbud transducer and clear voice transmission via a noise-cancelling microphone. Its lightweight design allows all-day use without wearing fatigue.



# Key Features

## Premium all-day comfort with a lightweight design

Lightweight construction reduces wearing fatigue while a soft earhook and exchangeable silicone tips ensure great comfort and fit.

## Tailored customization options for EPOS PTTs

The bottom cable can be pre-configured to operate with EPOS push-to-talk units, ensuring compatibility with existing equipment.

## Natural listening experience

EPOS Sound™ technology, integrated into this comfortable in-earbud, provides clear voice reception for optimal communication.

## Protect your hearing from sudden sound bursts

EPOS ActiveGard™ is a unique technology that protects your hearing from acoustic shock while preventing communication drop-out.

## Clear voice transmission for safe communication

The advanced noise-cancelling microphone effectively eliminates background noise, ensuring optimal voice and speech clarity.

# Additional benefits & features



## **Wearing flexibility**

The adjustable boom arm can be rotated for flexible wearing on either ear



## **Reduce acoustic brain fatigue**

Designed to provide the best conditions for your brain in noisy environments.



## **Removable earbud tips**

Provided silicone tips can be separated to adapt to any existing custom earpieces



## **Two-year warranty**

The headset is backed by EPOS two-year international warranty



## **Designed and tested to last**

A flexible boom arm and a secure interconnector make it a reliable working tool.

# Product data

1/2

Product	COMMAND 330 AG
Art. no.	1001242
EAN code	57 14708 01049 4
UPC code	8 40064 41049 6
General	
Wearing style	Single-sided
Ear coupling	In-Ear
Weight of headset	28 g / 0.98 oz
Storage temperature	-25 °C to +70 °C/ -13°F to +158 °F
Operating temperature	-15° C to + 60° C/ 5° F to + 140° F
Warranty	2 years

# Product data

2/2

## Speaker Specifications

Sound pressure level:

dB SPL @ 1 KHz, 0.5 V

105

dB SPL @ 1 KHz, 1 mW

104

dB SPL @ 1 KHz, 1V

88

Max SPL [dB]

105\*

THD, total harmonic distortion at 95 dB SPL at 1 kHz

< 1 %

Frequency response

80 - 16.0000 Hz

Impedance

150 Ω

\* Limited by EPOS ActiveGard®

# Product data

## Microphone Specifications

Microphone type	Electret
Sensitivity	-40 dB re. 1 V/Pa, +/- 2.5 dB
Pick-up pattern	Noise-cancelling, uni-directional
Supply voltage	1.5 - 9 VDC
Frequency response	100 - 10,000 Hz
Output voltage	10 mV/Pa
Recommended load resistance	150 - 2,200 $\Omega$

# Product data

## Packaging

Dimension of product packaging (W x H x D)	208 x 30 x 70 mm 8 x 1 x 2 in
Package weight (incl. complete product and packaging)	90.5 g / 31.92 oz
Units in distributor master carton	25
Master carton weight incl. products	2.69 kg / 5.93 lbs
Dimension of master carton (W x H x D)	370 x 180 x 220 mm 14.57 x 7.09 x 8.66 in
Unit pack/end user	1

## Product

COMMAND 330 AG

## What's in the box

Lightweight single-sided, in-ear headset, 1 x wind screen, 3 x earbud tips (S, M, L), Saftey Guide, Quick Guide